



# Container Specifications

Type	20' Dry	20' Dry	20' Seacell® Hi-cube	20' Dry Hi-cube	20' Flat Rack	20' Hi-cube Reefer
Prefix	PDLU1998 PDLU1999	PDLU200 PDLU300	GESU248 PDLU3100	PDLU320	PDLU500	PDLU700
ISO Code	2210/22G4	2210/22G4	2250/2EG1	2250/25G1	2261/22P3	2530/25R1
External Length	6,058 mm	6,058 mm	6,058 mm	6,058 mm	6,058 mm	6,058 mm
External Width	2,438 mm	2,438 mm	2,484 mm	2,438 mm	2,438 mm	2,438 mm
External Height	2,591 mm	2,591 mm	2,896 mm	2,896 mm	2,591 mm	2,896 mm
Internal Length	5,898 mm	5,898 mm	5,898 mm	5,898 mm	5,638 mm	5,456 mm
Internal Width	2,352 mm	2,352 mm	2,426 mm	2,352 mm	2,228 mm	2,290 mm
Internal Height	2,392 mm	2,395 mm	2,698 mm	2,700 mm	2,233mm	2,569 mm
Door Opening Width	2,340 mm	2,340 mm	2,375 mm	2,340 mm	–	2,294 mm
Door Opening Height	2,278 mm	2,280 mm	2,585 mm	2,585 mm	–	2,569 mm
Cubic Capacity	33.2 m <sup>3</sup>	33.2 m <sup>3</sup>	38.6 m <sup>3</sup>	37.4 m <sup>3</sup>	–	32.2 m <sup>3</sup>
Maximum Gross Weight	30,480 kg	30,480 kg	30,480 kg	30,480 kg	34,000 kg	30,480 kg
Tare	2,250 kg	2,185 kg	2,490 kg	2,315 kg	2,890 kg	3,330 kg
Payload	28,230 kg	28,295 kg	27,990 kg	28,165 kg	31,110 kg	27,150 kg
Type	40' Dry	40' Hi-Cube	40' Hi-Cube	40' Flatrack		
Prefix	PDLU4000	PDLU4000	PDLU4600	PDLU6000		
ISO Code	4300/42G1	4500/45G1	4500/45G1	4361/42P3		
External Length	12,192 mm	12,192 mm	12,192 mm	12,192 mm		
External Width	2,438 mm	2,438 mm	2,438 mm	2,438 mm		
External Height	2,591 mm	2,896 mm	2,896 mm	–		
Internal Length	12,034 mm	12,031 mm	12,031 mm	–		
Internal Width	2,352 mm	2,352 mm	2,352 mm	–		
Internal Height	2,395 mm	2,700 mm	2,700 mm	–		
Door Opening Width	2,343 mm	2,585 mm	2,585 mm	–		
Door Opening Height	2,280 mm	2,340 mm	2,340 mm	–		
Cubic Capacity	67.8 m <sup>3</sup>	76.4 m <sup>3</sup>	76.4 m <sup>3</sup>	–		
Maximum Gross Weight	32,500 kg	30,480 kg	32,500 kg	50,000 kg		
Tare	3,760 kg	3,890 kg	3,890 kg	4,900 kg		
Payload	28,740 kg	26,590 kg	28,610 kg	45,100 kg		

Note: These dimensions are intended as a guide only. Variations can occur between containers